



XPOWER

AXIAL FANS



X-47ATR

XPOWER Axial Fans - Efficient, Powerful + Lightweight

XPOWER's 14" and 18" Axial Fans feature powerful ventilation, with a special grille design that extends focused airflow up to 60 feet. Each axial fan includes a sealed motor, rugged ABS or ABS+PC housing for durability, and is stackable for easy transport. The rack allows 360° fan rotation for multiple drying positions.

X-47ATR (18" Diameter)

The X-47ATR provides maximum focused airflow up to 3600 CFM while using only 2.8A of power, allowing multiple units to be daisy chained using its built-in power outlet. Durable, lightweight, stackable ABS housing ensures easy transport and storage. Ducting hose and adapter kit are available for confined spaces and restoration jobs.

X-34 Series (14" Diameter)

The X-34 series compact axial fans are energy efficient, using only 1.6A of power, yet producing up to 1700 CFM. Motors are sealed for the professional water damage industry. Unique variable speed control feature allows precise airflow control, while a special grille design extends the focused airflow up to 60 ft. Model X-34ASR is mounted on a rust-resistant stainless steel rack.

- Sealed motor to resist corrosion in restoration applications
- Special grille design extends air to 60'
- 360° rotation for focused airflow
- Lightweight and stackable for easy transport
- Variable speed control
- Low power draw
- Daisy chain with circuit breaker and timer options

X-35AR (14" Diameter) & X-48ATR (18" Diameter) High Temperature Axial Fans

XPOWER's High Temp Fans has many of the same features as the X-34 and X-47 series, but are designed to withstand room temperatures up to 180° F when utilized in pest control applications and challenging environments. They feature powerful ventilation airflow up to 3600 CFM, and are constructed of durable, lightweight ABS + PC housing.

- Withstands heat up to 180° F
- Sealed motor to resist corrosion
- 360° rotation for focused airflow
- Variable speed control
- Lightweight and stackable for easy transport
- Daisy chain function with circuit breaker
- 3 hour timer option (X-48ATR only)



X-34AR

X-34TR



X-34ASR
(Stainless
Steel Rack)



X-35AR
(Hi-Temp)

X-48ATR
(Hi-Temp)



SPECIFICATIONS

Model No	X-34AR	X-34ASR	X-34TR	X-35AR (High Temp)	X-47ATR	X-48ATR (High Temp)
Volts/Hertz	115V/60Hz	115V/60Hz	115V/60Hz	115V/60Hz	115V/60Hz	115V/60Hz
Motor	1/4HP	1/4HP	1/4HP	1/4HP	1/3HP	1/3HP
Power	1.6A	1.6A	1.6A	1.6A	2.8A	2.8A
Rated Airflow	1720 CFM	1720 CFM	1720 CFM	1720 CFM	3600 CFM	3600 CFM
Speeds	Variable	Variable	Variable	Variable	Variable	Variable
Cord Length	20 ft.	20 ft.	10 ft.	20 ft.	20 ft.	20 ft.
Operating Position	360° Rotation 10" Height (Rack Included)	360° Rotation 10" Height (Rack Included)	360° Rotation 10" Height (Rack Included)	360° Rotation 10" Height (Rack Included)	360° Rotation 12.5" Height (Rack Included)	360° Rotation 12.5" Height (Rack Included)
Daisy Chain	Yes	Yes	No	Yes	Yes	Yes
3 Hour Timer	No	No	Yes	No	Yes	Yes
Stackable	Yes	Yes	Yes	Yes	Yes	Yes
Unit Weight	15.3lbs	17.8lbs	15.3lbs	17.1lbs	22.2lbs	26.6lbs
Unit Dimensions (LxWxH)	18.6"x9.4"x19.2"	18.6"x9.4"x19.2"	18.6"x9.4"x19.2"	18.6"x9.4"x19.2"	21.9"x9.8"x22.5"	21.9"x9.8"x22.5"
Box Weight	20.2lbs	21.7lbs	19.4lbs	20.2lbs	28.7lbs	31.6lbs
Box Dimensions (LxWxH)	19.7"x17.7"x10"	19.7"x17.7"x10"	19.7"x17.7"x10"	19.7"x17.7"x10"	22.6"x23.2"x11.4"	22.6"x23.2"x11.4"
Housing	ABS	ABS	ABS	ABS + PC	ABS	ABS + PC
Safety Certification	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL
Dual Thermal Protection	Yes	Yes	Yes	Yes	Yes	Yes
Pallet Qty	32 Units	32 Units	32 Units	32 Units	28 Units	28 Units

ACCESSORIES

Ducting Hose (Sold Separately)	N/A	N/A	N/A	N/A	16DH25 / 16DH15 - Yellow Polyester Ducting Hose Available in 25' & 15'x16" Ø Inside Diameter	N/A
Adapter Kit (Sold Separately)	N/A	N/A	N/A	N/A	16DHK Adapter Kit that Connects Ducting Hose to Axial Fan	N/A

PRODUCT FEATURES

Auxiliary Outlet with Circuit Breaker for Daisy Chain



Sealed Motor that Produces Efficient, Powerful and Quiet Airflow

Specially Designed Air Fin Guide for More Focused & Extended Airflow Range Up to 60 ft.

Stand-Alone Design with Rubber Footing that Works Even without Rack



3-Hour Timer & Variable Speed Control Switch

Durable ABS or ABS+PC Housing Design

Quick Release Knob for Easy Angle Adjustment

Wrap Around Cord Design

Fully Installed Rack / Stand Allowing 360° Angle Rotation



Stackable



Daisy Chain



Ducting Hose (X-47ATR Only)



Adapter Kit (X-47ATR Only)