




## F-8/F-16

### ULV (ULTRA LOW VOLUME) COLD FOGGER

The F-8 and F-16 ULV (ultra-low volume) cold fogger offers you ultimate performance in a small package. Featuring a light and compact design, this unit is ideal for full coverage for office, restaurants/food services, schools, hospitals, senior centers, pet boarding, greenhouse, and commercial properties. The reservoir incorporates an easy fill/tight cap and a reservoir level window to monitor your liquid levels. Applying disinfectants, sanitizers, and other solutions have never been easier than using the line of ULV cold foggers. With its powerful spray distance and ultra-small droplet size, this compact versatile unit is the industry leading choice for all your fogging needs.



**F-8 | F-16**  
Corded Models



# SPECIFICATIONS



Model No.	F-8	F-16
Voltz/Hertz	115V/60Hz	115V/60Hz
Motor	320W	500W
Power	3 Amps	4 Amps
Charge Time / Run Time	~	~
Speeds	1 Speed	2 Speed
Cord Length	20 ft.	25 ft.
Flow Rate	100ml/min & 200ml/min	250 ml/min
Spraying Distance	25+ ft.	30+ ft.
Average Droplet Size	< 50 Micron	< 50 Micron
Tank Capacity	800ml (27 fl oz.)	1600ml (54 fl oz.)
Battery Operated	No	No
Unit Weight	4.85 Lbs.	6.1 Lbs.
Unit Dimensions (LxWxH)	12.1x6.4x7.8 in.	14.6x6.8x8.3 in.
Housing	PP	PP
Thermal Protection	Yes	Yes



Droplet Size /  
Flow Rate Adjustment



Easy Fill Reservoir



2 Flow Rate Nozzles  
included in F-8 Models



Reservoir Level Window  
to Monitor Liquid Levels

