



| PREMIER®                               | 700 DF          |
|--|-----------------|
| BTU/HR rating                          | 700,000/350,000 |
| Heated air output (CFM)                | 5,000           |
| Fuel type                              | LP/NG           |
| Fuel consumption LP gas max (lbs/hr)   | 32.4/16.2       |
| Fuel consumption NG gas max (cu ft/hr) | 700/350         |
| Amps (start/continuous)                | 28/12           |
| Electric supply (volts/hz/phase)       | 240/60/1        |
| Motor horsepower                       | 1               |
| Running decibels                       | 70.4            |
| Unit length (in)                       | 47.5            |
| Unit width (in)                        | 28.0            |
| Unit height (in)                       | 69.0            |
| Shipping weight (lb)                   | 640             |
| Case material                          | Tri-Shield™***  |
| Electrical connection                  | Mounted inlet   |
| Thermostat connection                  | Mounted inlet   |
| Fork pockets                           | S               |
| Ventilation (fan only)                 | S               |
| Mobility kit (500-133766)              | O               |
| Gas hose, regulator & thermostat       | O               |
| Outlet duct diameter (in)              | 18              |
| Outlet duct max length (ft)            | 25              |
| Certified to ANSI/CSA standards        | U.S. & CA       |

S=Standard O=Optional

\* Amps spike over 15 during initial start-up. Check breaker capability.

\*\* 18.1 with optional thermostat bracket installed.

\*\*\* Tri-shield coated steel with three unique protective layers including: a non-corrosive hot-dipped, galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

### Accessories (sold separately):

- 500-133671, 2-1 Outlet adapter for 24" duct
- 500-22835, Duct, 18" x 12' w/ duct adapter & clamp
- 500-133767, Duct, 24" x 25' w/ duct adapter & clamp
- 500-132976, T-Stat with 1.4' cord
- 500-132047, Hose, 1" x 15', 1 NPT both ends
- 500-132136, Regulator, NG
- 500-25141, Regulator, LP
- 500-133766, Mobility Kit

CA RESIDENTS:



**WARNING**

Cancer and reproductive harm. See  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).