SELF-CONTAINED HEATER TRAILERS

TURNKEY PORTABLE HEAT AND POWER

Self-contained heaters work well for remote applications that require heat where a jobsite power source is unavailable. Standard features include a solid steel welded channel frame and floor, electric emergency second axle brakes, as well as safety chains, ball, or pintle hitch and jack.

FEATURES

Diesel Engine

Engine features include electric start/ glow plugs, battery charging alternator, heavy duty radiator, and air cleaner.

Built-In Generator

Generator is single phase, 120V, contains instrument panel (with keyed ignition and hour meter), and 8 kW at 1,800 RPM (14HP).

On-Board Fuel Tank

Fuel tank is a TC approved steel tank with 2" fuel inlet nozzle mounted at the side of the trailer for ground access.



ENGINE	YANMAR OR KUBOTA LIQUID COOLED DIESEL	
HEATERS	(2)390,000BTU INDIRECT FIRED HEATERS	
FUEL CONSUMPTION	ENGINE: 1.08 GAL/HR AT FULL LOAD HEATERS: (2) 400,000 BTU AT 2.75 GAL/HR	
RUN TIME	44 HRS	
GENERATOR	STAMFORD NEWAGE	
FUEL TANK*	300 GALLONS	
BURNER TECHNOLOGY	RIELLO BURNER	
LxWxH	15' x 7'4" x 7'	
WEIGHT	4,300 LBS (EMPTY)	
APPROVALS	CSA & ESA APPROVED DOT APPROVED TRAILER	